

Code: 144-10



Golden  
World  
Trading  
Group

[www.GoldenWTG.org](http://www.GoldenWTG.org)



**Xingtai Tractor**

<b>Horsepower:</b>	12HP/8.1KW
<b>Product Model:</b>	XT120
<b>Outer Size(mm):</b>	2315*1200*1285
<b>G.W/N.W (kg):</b>	1035/930
<b>Wheel base L(mm):</b>	1398
<b>Startup Mode:</b>	hand-start
<b>Clutch:</b>	dry single disc clutch with single function
<b>Minimun Ground Clearance(mm)</b>	260
<b>Minimun Turning Radius(m)</b>	3.5
<b>Calibration Traction(KN)</b>	3.1

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



**Xingtai Tractor**

<b>Horsepower:</b>	25HP/18.4KW
<b>Product Model:</b>	XT250
<b>Outer Size(mm):</b>	2870*1200*1285
<b>G.W (kg):</b>	1220
<b>Wheel base L(mm):</b>	1550
<b>Startup Mode:</b>	electric-start
<b>Clutch:</b>	dry single disc clutch with single function
<b>Minimun Ground Clearance(mm)</b>	355
<b>Minimun Turning Radius(m)</b>	4.2
<b>Calibration Traction(KN)</b>	5.2

**Drive : 2WD**

**Transmission Gear:** eight forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	12HP/8.1KW
Product Model:	XT120D
Outer Size(mm):	2315*1200*1285
G.W/N.W (kg):	1035/930
Wheel base L(mm):	1398
Startup Mode:	electric-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	260
Minimun Turning Radius(m)	3.5
Calibration Traction(KN)	3.1

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	16HP/11.76KW
Product Model:	XT160
Outer Size(mm):	2315*1200*1285
G.W/N.W (kg):	1035/930
Wheel base L(mm):	1398
Startup Mode:	hand-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	260
Minimun Turning Radius(m)	3.9
Calibration Traction(KN)	3.3

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	18HP/13.2KW
Product Model:	XT180
Outer Size(mm):	2500*1210*1290
G.W/N.W (kg):	1220
Wheel base L(mm):	1550
Startup Mode:	electric-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	355
Minimun Turning Radius(m)	3.9
Calibration Traction(KN)	3.7

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	20HP/14.7KW
Product Model:	XT200
Outer Size(mm):	2330*1200*1285
G.W/N.W (kg):	1220
Wheel base L(mm):	1550
Startup Mode:	electric-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	306
Minimun Turning Radius(m)	3.9
Calibration Traction(KN)	4.6

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force





### Xingtai Tractor

Horsepower:	22HP/16.2KW	
Product Model:	XT220	
Outer Size(mm):	2500*1210*1290	
G.W/N.W (kg):	1220	
Wheel base L(mm):	1550	
Startup Mode:	electric-start	
Clutch:	dry single disc clutch with single function	
Minimun Ground Clearance(mm)		305
Minimun Turning Radius(m)		3.9
Calibration Traction(KN)		4.6

**Drive : 2WD**

**Transmission Gear:**

six forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



### Xingtai Tractor

Horsepower:	16HP/11.76KW	
Product Model:	XT160D	
Outer Size(mm):	2315*1200*1285	
G.W/N.W (kg):	1035/930	
Wheel base L(mm):	1398	
Startup Mode:	hand-start	
Clutch:	dry single disc clutch with single function	
Minimun Ground Clearance(mm)		260
Minimun Turning Radius(m)		3.9
Calibration Traction(KN)		3.3

**Drive : 2WD**

**Transmission Gear:**

six forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	18HP/13.2KW
Product Model:	XT180D
Outer Size(mm):	2315*1210*1270
G.W/N.W (kg):	1035/930
Wheel base L(mm):	1398
Startup Mode:	electric-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	260
Minimun Turning Radius(m)	3.9
Calibration Traction(KN)	3.5

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	12HP/8.1KW
Product Model:	XT120
Outer Size(mm):	2315*1200*1285
G.W/N.W (kg):	1035/930
Wheel base L(mm):	1398
Startup Mode:	hand-start
Clutch:	dry single disc clutch with single function
Minimun Ground Clearance(mm)	260
Minimun Turning Radius(m)	3.5
Calibration Traction(KN)	3.1

**Drive : 2WD**

**Transmission Gear:** six forward gears,two reverse gears, with High and Low choice

### The Main Technical Specification

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force

	<b>Xingtai Tractor</b>		
	<b>Horsepower:</b>	16HP/11.76KW	
	<b>Product Model:</b>	XT160	
	<b>Outer Size(mm):</b>	2315*1200*1285	
	<b>G.W/N.W (kg):</b>	1035/930	
	<b>Wheel base L(mm):</b>	1398	
	<b>Startup Mode:</b>	hand-start	
	<b>Clutch:</b>	dry single disc clutch with single function	
	<b>Minimun Ground Clearance(mm)</b>	260	
	<b>Minimun Turning Radius(m)</b>	3.9	
<b>Calibration Traction(KN)</b>	3.3		
<b>Drive : 2WD</b>			

<b>Transmission Gear:</b>	six forward gears,two reverse gears, with High and Low choice
<b>The Main Technical Specification</b>	<ol style="list-style-type: none"> <li>1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder</li> <li>2.No posture,full gear drive directly</li> <li>3.Accord with international standard power output shaft</li> <li>4.Gear pump hydraulic hoisting system,lifting force meet international standard</li> <li>5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force</li> </ol>

	<b>Xingtai Tractor</b>		
	<b>Horsepower:</b>	18HP/13.2KW	
	<b>Product Model:</b>	XT180	
	<b>Outer Size(mm):</b>	2500*1210*1290	
	<b>G.W/N.W (kg):</b>	1220	
	<b>Wheel base L(mm):</b>	1550	
	<b>Startup Mode:</b>	electric-start	
	<b>Clutch:</b>	dry single disc clutch with single function	
	<b>Minimun Ground Clearance(mm)</b>	355	
	<b>Minimun Turning Radius(m)</b>	3.9	
<b>Calibration Traction(KN)</b>	3.7		
<b>Drive : 2WD</b>			

<b>Transmission Gear:</b>	six forward gears,two reverse gears, with High and Low choice
<b>The Main Technical Specification</b>	<ol style="list-style-type: none"> <li>1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder</li> <li>2.No posture,full gear drive directly</li> <li>3.Accord with international standard power output shaft</li> <li>4.Gear pump hydraulic hoisting system,lifting force meet international standard</li> <li>5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force</li> </ol>





## Xingtai Tractor

Horsepower:	20HP/14.7KW	
Product Model:	XT200	
Outer Size(mm):	2330*1200*1285	
G.W/N.W (kg):	1220	
Wheel base L(mm):	1550	
Startup Mode:	electric-start	
Clutch:	dry single disc clutch with single function	
Minimum Ground Clearance(mm)		306
Minimum Turning Radius(m)		3.9
Calibration Traction(KN)		4.6

**Drive : 2WD**

**Transmission Gear:**

six forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force



## Xingtai Tractor

Horsepower:	25HP/18.4KW	
Product Model:	XT250	
Outer Size(mm):	2870*1200*1285	
G.W (kg):	1220	
Wheel base L(mm):	1550	
Startup Mode:	electric-start	
Clutch:	dry single disc clutch with single function	
Minimum Ground Clearance(mm)		355
Minimum Turning Radius(m)		4.2
Calibration Traction(KN)		5.2

**Drive : 2WD**

**Transmission Gear:**

eight forward gears,two reverse gears, with High and Low choice

**The Main Technical Specification**

- 1.vertical,water-cooled,dieseled and four stroked. electric-start or hang-start,single-cylinder or double cylinder
- 2.No posture,full gear drive directly
- 3.Accord with international standard power output shaft
- 4.Gear pump hydraulic hoisting system,lifting force meet international standard
- 5.Compact structure,beautiful,practical;low energy consumption,high effect,strong traction,powerful climbing force