

Orbita RFID Access

Fancy Features:

To show room number, status of batteries, time and date.

Indication of lock status such as "Welcome", "Don't Disturb", "Wrong card"...

etc. And error self-detective info is available as well.



TECHNICAL PARAMETERS

Dimension of External Panel:	L285mm*W74.5mm*H13mm
Material:	Stainless Steel, Moisture Proof, Fire Retardant
Working Voltage:	DC6V or 4 AA Alkaline batteries
Power Consumption:	Static Load<10Ua Dynamic Load 100~150Ma
Working Environment:	Working Humidity: 20%~90% Working Temperature: -50℃~60℃
Keycard Option:	Mifare 1 card

FUNCTIONAL CHARACTERISTICS

Interface with most of the PMS systems, Fidelio/Opera registered!
CE & FCC Certified!

Brushed stainless steel color lasts more than 10 years

ANSI Standard mortise

Inside Dead Bolt. Inside handle retracts latches and deadbolt.

Mifare 1K card, compatible with Mifare Energy Saver

Override Computer Key for Emergency use, individual or master cylinder

Lost guest card suspension simply by issuing a new guest card with suspending function

Lock operation record printable: 240 pcs or more

Power: 4pcs #5 AA Alkaline batteries. 18 months' duration

Low battery voltage warning. (Lower than 3.5 V.)

Self Error detecting by LED and "beep"

Improper lock warning

Passage function available

Can be integrated with 16 public areas such as Lift/Parking/Swimming Pool/Sauna Room/Tennis court/Gym ...etc.

Integrated with Lift/Elevator with two options:

RFID reader to control power like a switch, only cards issued from hotel can work on it, guests can go to any floor.



RFID reader and controlling box to control lift Floor by Floor, guests can only go to their own floors.

