

Code: 144-11



Golden
World
Trading
Group

www.GoldenWTG.org



D800-A



D900-A



❖ Product Details:

- ❖ Type: Tractor
- ❖ By wheel: 2WD
- ❖ Usage: Farm Tractor
- ❖ Brand Name: Dioo
- ❖ Model Number: D800-A; D900-A
- ❖ Place of Origin: Weifang, China (mainland)
- ❖ Condition: New

Payment & Shipping terms:

- Price: [Get latest price](#)
- Minimum order quantity: 1 unit/units
- Port: China port
- Packaging details: standard export packing roll-roll or disassembled in one 40' container.

- Payment terms :Irrevocable L/C at sight, TT
- Supply ability: 100 unit/units per month
- Delivery time: 30 days after the receipt of deposit



D800-A



D900-A



- ❖ **Power Strong**
- ❖ Dongfanhong engine is optional for installation, to guarantee dust emission standard.
- ❖ Advanced Technology
- ❖ Employed strengthened drive axle, Germany imported dual action LUK clutch, with performance more reliable; dual cylinder pressure lifter with height limitation.
- ❖ **High Efficiency**
- ❖ 16+8 shuttle-type gear shift is employed, several gears for the option such as: 8+4, 16+8(creep gear)
- ❖ 150L dual underneath-type cylinder is employed to meet the demand of operation.
- ❖ **Comfortable**
- ❖ Employed side-installed operation, shifts of sliding sleeve and hydraulic steering gear.

D900-A Standard configuration and technical data

Item	Technical Data
Type	4×2WD
Nominated traction force (KN)	17.7
Length (MM)	4530
Width (MM)	1986
Height (MM)	2760
Wheelbase (MM)	2195/2366
Wheelbase of front wheel (MM)	1385-1685
Wheelbase of rear wheel (MM)	1608-1996
Power of engine (KW)	66.2
Power Output Shaft (r/min)	760/1000;540/1000、540/760、760/850 for the option
Gear shift	16+8 shuttle-type gear shift
Speed range/ forward (km/h)	1.58~33.69 (16+8 shuttle-type gear shift) /0.4~34.9 (16+8 creep gear) /2.2~34.9 (8+4 shift)
Speed range/ backward (km/h)	2.41~34.67 (16+8 shuttle-type gear shift) /0.6~10.8 (16+8 creep gear) /3.0~10.8 (8+4 shift)



D1004-A



Product Details:

Type: Wheel Tractor

By wheel: 4WD

Usage: Farm Tractor

Brand Name: Dioo

Model Number: D1004-A

Place of Origin: Weifang, China (mainland)

Condition: New

Payment & Shipping terms:

Price: [Get latest price](#)

Minimum order quantity: 1 unit/units

Port: China port

Packaging details: standard export packing roll-roll or disassembled in One 40' Container.

Delivery time: 30 days after the receipt of deposit

Payment terms: LC TT

Supply ability: 100 Unit/units per month



D1004-A



Advanced Technology

Employed strengthened drive axel, Germany imported dual action LUCK clutch, with performance more reliable; dual cylinder lifter with height limitation.

High Efficiency

16+8 shuttle-type gear shift is employed, several gears for the option such as: 8+4,16+8(creep gear)

150L dual underneath-type cylinder is employed to meet the demand of operation.

Dongfanhong engine is optional for installation, to guarantee dust emission standard.

Comfortable

Employed side-installed operation, shifts of sliding sleeve and hydraulic steering gear.

Dioo D1004-A

Item	Technical Date
Type	4×4WD
Nominated traction force (KN)	23.7
Length (MM)	4530
Width (MM)	2050
Height (MM)	2810
Wheelbase (MM)	2195/2366
Wheelbase of front wheel (MM)	1610-1950
Wheelbase of rear wheel (MM)	1608-1996
Power of engine (KW)	73.5
Power output shaft (r/min)	760/1000;540/1000、540/760、760/850 for the option
Gear shift	16+8 shuttle-type gear shift
Speed range/forward (km/h)	1.58~33.69 (16+8 shuttle-type gear shift) /0.4~34.9 (16+8 creep gear) /2.2~34.9 (8+4 shift)
Speed range/backward (km/h)	2.41~34.67 (16+8 shuttle-type gear shift) /0.6~10.8 (16+8 creep gear) /3.0~10.8 (8+4 shift)



O1254-G



❖ **Product Details:**

- ❖ Type: Wheel Tractor
- ❖ By wheel: 2WD
- ❖ Usage: Farm Tractor
- ❖ Brand Name: Dioo
- ❖
- ❖ Model Number: O1254-G
- ❖ Place of Origin: Weifang, China (mainland)
- ❖ Condition: New
- ❖

Payment & Shipping terms:

- Price: [Get latest price](#)
- Minimum order quantity: 1 unit/units
- Port: China port
- Packaging details: standard export packing roll-roll or disassembled in one 40' container.

- Payment terms :Irrevocable L/C at sight, TT
- Supply ability: 100 unit/units per month
- Delivery time: 30 days after the receipt of deposit

Product characteristics: 1. Equipped with 125HP Yuchai engine, with torque reserve large, power strong, and oil consumption low, Yuchai turbocharged engine is optional for installation. To meet the demand of different users. Updated power discharge, updated performance, with oil consumption low and performance more reliable.

2. Synchronizer's shuttle-type gear shift device employ bevel gear transmission, which helps reliability and flexibility, Employed Germany original LUK clutch and CARRARO front drive axle, with operation more flexible and performance more reliable, Employed cardan joint front drive axle, with large transfer torque and more reliable performance; Hydraulic system, with performance more reliable.

3. 16+8 shuttle-type gear shift is employed, with speed matching reasonable and work efficiency high. 320L large reserves of fuel tank, with continual operating time long, suspension mechanism of category II to meet the match with several agricultural machines, with work efficiency high.

4. The complete vehicle enjoys prominent performance and advanced structure, fashionable streamline outline design. Full-sealed cab, and devices like air conditioning, warm air system, and audio system are optional for installation, and the complete vehicle is luxurious and comfortable. Electronic-control lifter, with operation flexible and comfortable.



Dioo O1254-G

Item	Technical Data
Type	4WD
Nominated traction force(KN)	28
Length (MM)	5250
Width (MM)	2400
Height (MM)	3030
Wheelbase (MM)	2688
Wheelbase of front wheel (MM)	1900
Wheelbase of rear wheel (MM)	Single tire type: 1750; Dual tire type: 2330
Power of engine (KW)	92
Power output shaft (r/min)	540/1000;760/1000 for the option
Gear shift	16+16
Speed range/forward (km/h)	3.42~34.03 (16+16 shift)
Speed range/backward (km/h)	2.33~23.22 (16+16 shift)



O1604-G



Product Details:

Type: Wheel Tractor

By wheel: 4WD

Usage: Farm Tractor

Brand Name: Dioo

Model Number: O1604-G

Place of Origin: Weifang, China (mainland)

Condition: New

Payment & Shipping terms:

Price: [Get latest price](#)

Minimum order quantity: 1 unit/units

Port: China port

Packaging details: standard export packing roll-roll or disassembled in One 40' Container.

Delivery time: 30 days after the receipt of deposit

Payment terms: LC TT

Supply ability: 100 Unit/units per month

未来主流机型

1604

配套高端农机具

实力企业巨献



O1604-G

D
i
o
o

B
r
a
n
d



Product characteristics

Power Strong

Equipped with domestically renowned Shanghai D6114 diesel engine.

Comfortable

Imported front drive axel
New full-sealed cab, equipped with heating and ventilation devices and air conditioner, with modeling elegant and vision broadened

High Efficiency

Many shifts of transmission, wide range of speed and with farm work efficiency high
Rear wheel tread is not adjustable
Full hydraulic steering with security reliable

Advanced Technology

Activated shoe type brake structure with brake reliable, secure and flexible.
Differential lock: electric hydraulic control s employed.
Main clutch: pneumatic booster pedal type hydraulic control; Vice-clutch : EHC s employed
large volume of fuel tank
dual rear-tire configuration is optional for installation
standard configuration 3 pieces of multiway valve and import quick change joint to control folded rake and reversible plough
the complete vehicle with large traction to control large-scale agriculture implement compound operation.
hydraulic lifting system:

未来主流机型

1604

配套高端农机具 实力企业巨献

Dioo O1604-G

Item	Technical Data
Type	4X4WD
Overall dimensions(LXWXH)(mm)	5285x2696x2945
Wheelbase(mm)	2848
Min. ground clearance (mm)	459
Min. operating mass (Kg)	6740
Type spec. front/rear	14.9-28/18.4-38
Wheel tread, front/rear	1680-2176/1620-2200
Gear shift, forward/backward	12/4
Speed range (km/h) forward/backward	2.25-29.06/4.25-11.47
PTO power(KW)	106
Lifting force (KN)	36
Diesel engine	
model	SC8D 190.1G2
Type	Six cylinder, vertical, water cooled, four stroke, direct injection, turbocharged
Displacement (L)	8.27
Rated power/speed(KW) (r/min)	117.6/2200