

Code: 107-2



Golden
World
Trading
Group

www.GoldenWTG.org

汽油机

GASOLINE ENGINE

▶ CS120

▶ CS160

▶ CS200



技术规格 Specifications

型号 Model	CS120	CS160	CS200
发动机型式 (Engine type)	单缸、四冲程、气缸中心斜置25° 4-stroke, 25° inclined, single cylinder with Air-cooled		
缸径 × 行程 Bore × Stroke (mm × mm)	60 × 42	68 × 45	68 × 54
气缸排量 Displacement(ml)	118	163	196
压缩比 Compression ratio	8.5: 1		
最大输出功率 Max.output (HP/rpm)	4.0/3600	5.5/3600	6.5/3600
最大扭矩 Max.torque (N.m/rpm)	7.4/2500	10.8/2500	13/2500
点火系统 Ignition system	无触点晶体管点火T.C.I		
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start		
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type		
燃油箱容量 Fuel tank capacity(L)	2.5	3.6	3.6
耗油量 Fuel consumption(g/HP.h)	270		
机油容量 Engine oil capacity(L)	0.6		
尺寸Dimensions(L×W×H)(mm×mm×mm)	387 × 330 × 360		
净重 Net weight(Kg)	13	15	16

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

汽油机

GASOLINE ENGINE

▶ CS240

▶ CS270



技术规格 Specifications

型号 Model	CS240	CS270
发动机型式 (Engine type)	单缸、四冲程、气缸中心斜置25° 4-stroke, 25° inclined, single cylinder with Air-cooled	
缸径 × 行程 Bore × Stroke (mm × mm)	73 × 58	77 × 58
气缸排量 Displacement(ml)	242	270
压缩比 Compression ratio	8.2: 1	
最大输出功率 Max.output (HP/rpm)	8.0/3600	9.0/3600
最大扭矩 Max.torque (N.m/rpm)	16.7/2500	19/2500
点火系统 Ignition system	无触点晶体管点火T.C.I	
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start	
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type	
燃油箱容量 Fuel tank capacity(L)	6	
耗油量 Fuel consumption(g/HP.h)	260	
机油容量 Engine oil capacity(L)	1.1	
尺寸 Dimensions(L × W × H)(mm × mm × mm)	460 × 380 × 410	
净重 Net weight(Kg)	25	

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

汽油机

GASOLINE ENGINE

▶ CS340

▶ CS390



技术规格 Specifications

型号 Model	CS340	CS390
发动机型式 (Engine type)	单缸、四冲程、气缸中心斜置25° 4-stroke, 25° inclined, single cylinder with Air-cooled	
缸径 × 行程 Bore × Stroke (mm × mm)	82 × 64	88 × 64
气缸排量 Displacement(ml)	337	389
压缩比 Compression ratio	8.0: 1	
最大输出功率 Max.output (HP/rpm)	11.0/3600	13.0/3600
最大扭矩 Max.torque (N.m/rpm)	23.5/2500	26.4/2500
点火系统 Ignition system	无触点晶体管点火T.C.I	
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start	
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type	
燃油箱容量 Fuel tank capacity(L)	6.5	
耗油量 Fuel consumption(g/HP.h)	260	
机油容量 Engine oil capacity(L)	1.1	
尺寸 Dimensions(L × W × H)(mm × mm × mm)	530 × 405 × 480	
净重 Net weight(Kg)	31	

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

双链条减速汽油机

GASOLINE ENGINE

WITH CHAIN REDUCTION



▶ CS160SL

▶ CS200SL

技术规格 Specifications

型号 Model	CS160SL	CS200SL
发动机型式 (Engine type)	单缸、四冲程、气缸中心斜置25° 4-stroke, 25° inclined, single cylinder with Air-cooled	
缸径 × 行程 Bore × Stroke (mm × mm)	68 × 45	68 × 54
气缸排量 Displacement(ml)	163	196
压缩比 Compression ratio	8.5: 1	
最大输出功率 Max.output (HP/rpm)	5.5/1800	6.5/1800
最大扭矩 Max.torque (N.m/rpm)	21.6/1250	26/1250
点火系统 Ignition system	无触点晶体管点火T.C.I	
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start	
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type	
燃油箱容量 Fuel tank capacity(L)	3.6	
耗油量 Fuel consumption(g/HP.h)	270	
机油容量 Engine oil capacity(L)	0.6	
尺寸 Dimensions(L × W × H)(mm × mm × mm)	387 × 360 × 360	
净重 Net weight(Kg)	17	18

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

离合器减速汽油机

GASOLINE ENGINE

WITH CLUTCH REDUCTION



➤ CS160C

➤ CS200C

➤ CS240C

➤ CS270C

技术规格 Specifications

型号 Model	CS160C	CS200C	CS240C	CS270C
发动机型式 (Engine type)	单缸、四冲程、气缸中心斜置25° 4-stroke, 25° inclined, single cylinder with Air-cooled			
缸径 × 行程 Bore × Stroke (mm × mm)	68 × 45	68 × 54	73 × 58	77 × 58
气缸排量 Displacement(ml)	163	196	242	270
压缩比 Compression ratio	8.5: 1		8.2: 1	
最大输出功率 Max.output (HP/rpm)	5.5/1800	6.5/1800	8.0/1800	9.0/1800
最大扭矩 Max.torque (N.m/rpm)	21.6/1250	26/1250	33.4/1250	38/1250
点火系统 Ignition system	无触点晶体管点火T.C.I			
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start			
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type			
燃油箱容量 Fuel tank capacity(L)	3.6		6.0	
耗油量 Fuel consumption(g/HP.h)	270		260	
机油容量 Engine oil capacity(L)	0.6		1.1	
尺寸 Dimensions(L×W×H)(mm×mm×mm)	377 × 407 × 370		470 × 470 × 445	
净重 Net weight(Kg)	17	18	27	27

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR

 CG950



技术规格 Specifications

发电机 GENERATOR	型号Model	CG950
	类型Type	单相 single-phase
	电压调节Voltage regulate	电容 Capacitor
	频率Frequency (Hz)	50/60
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240
	额定交流输出功率Rated AC Output(KVA)	0.65/0.75
	最大交流输出功率Peak AC Output(KVA)	0.8/0.95
	功率因数Power factor	COS φ =1
发动机 ENGINE	型号Model	1E45F
	类型Type	强制空冷, 两冲程 Forced Air-cooled 2-Stroke
	排气量Displacement(ml)	62.8
	最大输出功率Max.output(HP/rpm)	1.8/3600
	燃料Fuel	90#汽油与二冲程汽油机专用机油, 容积混合比为50: 1 Mixing rate between 90# gasoline and two-stroke oil 50:1
	燃油箱容量Fuel tank capacity(L)	4
	连续工作时间 Continuous operating hours(h)	13.5
	点火系统Ignition system	电子点火 C.D.I
	启动系统 Starting system	反冲手拉起动Recoil and hand-operated
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	68
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	385 x 335 x 340
	净重 Net weight(kg)	20.5
	毛重Gross weight(kg)	22.5

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR

 CG1000



技术规格 Specifications

发电机 GENERATOR	型号Model	CG1000
	类型Type	单相 single-phase
	电压调节Voltage regulate	自动电压调节 AVR
	频率Frequency (Hz)	50/60
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240
	额定交流输出功率Rated AC Output(KVA)	0.85/1.0
	最大交流输出功率Peak AC Output(KVA)	1.0/1.1
	功率因数Power factor	COS φ =1
发动机 ENGINE	型号Model	CS154
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke
	排气量Displacement(ml)	86.5
	最大输出功率Max.output(HP/rpm)	2.8/3600
	燃料Fuel	无铅汽油 Unleaded gasoline
	燃油箱容量Fuel tank capacity(L)	5
	连续工作时间 Continuous operating hours(h)	15
	点火系统Ignition system	电子点火 C.D.I
	启动系统Starting system	反冲手拉起动Recoil and hand-operated
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	68
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	457 x 363 x 390
	净重 Net weight(kg)	30
	毛重Gross weight(kg)	31

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

便携式汽油发电机组

PORTABLE GENERATOR

 CG1000SE



技术规格 Specifications

发电机 GENERATOR	型号Model	CG1000SE
	类型Type	单相 single-phase
	电压调节Voltage regulate	自动电压调节 AVR
	频率Frequency (Hz)	50/60
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240
	额定交流输出功率Rated AC Output(KVA)	0.85/1.0
	最大交流输出功率Peak AC Output(KVA)	1.0/1.1
	功率因数Power factor	COS ϕ =1
发动机 ENGINE	型号Model	CS154
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke
	排气量Displacement(ml)	86.5
	最大输出功率Max.output(HP/rpm)	2.8/3600
	燃料Fuel	无铅汽油 Unleaded gasoline
	燃油箱容量Fuel tank capacity(L)	4.2
	连续工作时间 Continuous operating hours(h)	12
	点火系统Ignition system	电子点火 C.D.I
	启动系统 Starting system	反冲手拉起动Recoil and hand-operated
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	68
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	485 x 360 x 395
	净重 Net weight(kg)	24
	毛重Gross weight(kg)	26

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR



➤ CG2000WS

➤ CG2500WS

➤ CG3500WS

技术规格 Specifications

发电机 GENERATOR	型号Model	CG2000WS	CG2500WS	CG3500WS
	类型Type	单相 single-phase		
	电压调节Voltage regulate	自动电压调节 AVR		
	频率Frequency (Hz)	50/60		
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240		
	额定交流输出功率Rated AC Output(KVA)	1.5/1.8	2.0/2.2	2.5/2.8
	最大交流输出功率Peak AC Output(KVA)	1.8/2.0	2.2/2.5	2.8/3.0
	功率因数Power factor	COS φ=1		
发动机 ENGINE	型号Model	CS160	CS200	CS200
	类型Type	强制风冷, 四冲程 OHV Forced Air-cooled 4-Stroke		
	排气量Displacement(ml)	163	196	196
	最大输出功率Max.output(HP/rpm)	5.5/3600	6.5/3600	6.5/3600
	燃料Fuel	无铅汽油 Unleaded gasoline		
	燃油箱容量Fuel tank capacity(L)	15		
	连续工作时间 Continuous operating hours(h)	13	12	11
	点火系统Ignition system	无触点晶体管点火 T.C.I		
	启动系统 Starting system	反冲手拉启动/电启动Recoil and hand-operated/ Electric start		
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	68		
	包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	600 x 450 x 470	
净重 Net weight(kg)		39	40	48
毛重Gross weight(kg)		41	42	52

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR

- CG3800WS
- CG4000WS
- CG5000WS
- CG6500WS



技术规格 Specifications

发电机 GENERATOR	型号Model	CG3800WS	CG4000WS	CG5000WS	CG6500WS
	类型Type	单相 single-phase			
	电压调节Voltage regulate	自动电压调节 AVR			
	频率Frequency (Hz)	50/60			
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240			
	额定交流输出功率Rated AC Output(KVA)	3.0/3.5	3.5/3.8	4.0/4.5	5.0/5.5
	最大交流输出功率Peak AC Output(KVA)	3.3/3.8	3.8/4.0	4.5/5.0	5.5/6.5
	功率因数Power factor	COS φ=1			
发动机 ENGINE	型号Model	CS240	CS270	CS340	CS390
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke			
	排气量Displacement(ml)	242	270	337	389
	最大输出功率Max.output(HP/rpm)	8.0/3600	9.0/3600	11.0/3600	13.0/3600
	燃料Fuel	无铅汽油 Unleaded gasoline			
	燃油箱容量Fuel tank capacity(L)	25			
	连续工作时间 Continuous operating hours(h)	12.5	11	10	9
	点火系统Ignition system	无触点晶体管点火 T.C.I			
	启动系统Starting system	反冲手拉启动/电启动Recoil and hand-operated/ Electric start			
	操作噪声等级 (7米) Operating noise level(7m)dB(A)	72			
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L × W × H(mm × mm × mm)	700 × 565 × 590			
	净重 Net weight(kg)	65	70	74	82
	毛重Gross weight(kg)	69	74	78	86

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR



➤ CG2000

➤ CG2500

➤ CG3500

技术规格 Specifications

发电机 GENERATOR	型号Model	CG2000	CG2500	CG3500
	类型Type	单相 single-phase		
	电压调节Voltage regulate	自动电压调节 AVR		
	频率Frequency (Hz)	50/60		
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240		
	额定交流输出功率Rated AC Output(KVA)	1.5/1.8	2.0/2.2	2.5/2.8
	最大交流输出功率Peak AC Output(KVA)	1.8/2.0	2.2/2.5	2.8/3.0
	功率因数Power factor	COS φ=1		
发动机 ENGINE	型号Model	CS160	CS200	CS200
	类型Type	强制风冷, 四冲程 OHV Forced Air-cooled 4-Stroke		
	排气量Displacement(ml)	163	196	196
	最大输出功率Max.output(HP/rpm)	5.5/3600	6.5/3600	6.5/3600
	燃料Fuel	无铅汽油 Unleaded gasoline		
	燃油箱容量Fuel tank capacity(L)	15		
	连续工作时间 Continuous operating hours(h)	13	12	11
	点火系统Ignition system	无触点晶体管点火 T.C.I		
	启动系统 Starting system	反冲手拉起动/电起动Recoil and hand-operated/ Electric start		
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	68		
	包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	600 x 450 x 470	
净重 Net weight(kg)		39	40	48
毛重Gross weight(kg)		41	42	52

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油发电机组

GASOLINE GENERATOR

➤ CG3800

➤ CG4000

➤ CG5000

➤ CG6500



技术规格 Specifications

发电机 GENERATOR	型号Model	CG3800	CG4000	CG5000	CG6500
	类型Type	单相 single-phase			
	电压调节Voltage regulate	自动电压调节 AVR			
	频率Frequency (Hz)	50/60			
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240			
	额定交流输出功率Rated AC Output(KVA)	3.0/3.5	3.5/3.8	4.0/4.5	5.0/5.5
	最大交流输出功率Peak AC Output(KVA)	3.3/3.8	3.8/4.0	4.5/5.0	5.5/6.5
	功率因数Power factor	COS $\varphi=1$			
发动机 ENGINE	型号Model	CS240	CS270	CS340	CS390
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke			
	排气量Displacement(ml)	242	270	337	389
	最大输出功率Max.output(HP/rpm)	8.0/3600	9.0/3600	11.0/3600	13.0/3600
	燃料Fuel	无铅汽油 Unleaded gasoline			
	燃油箱容量Fuel tank capacity(L)	25			
	连续工作时间 Continuous operating hours(h)	12.5	11	10	9
	点火系统Ignition system	无触点晶体管点火 T.C.I			
	启动系统 Starting system	反冲手拉起动/电起动Recoil and hand-operated/ Electric start			
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	72			
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	700 x 535 x 590			
	净重 Net weight(kg)	65	70	74	82
	毛重Gross weight(kg)	69	74	78	86

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

汽油水泵机组

WATER PUMP

➤ WP20

➤ WP30

➤ WP40



技术规格 Specifications

机型 Water pump model		WP20	WP30	WP40
水泵 WATER PUMP	进、出水管内径 Inlet and outlet inside diameter (mm)	50 (2 inch)	80 (3 inch)	100 (4 inch)
	扬程 Pump lift (m)	26	28	16
	吸程 Suction height (m)	8	8	8
	最大抽水量 Max.pump output (L/min)	550	1000	1300
发动机 ENGINE	型号Model	CS160	CS200	CS240
	连续工作时间 Continuous operating hours(h)	2.8	2.4	2.4
	燃油箱容量Fuel tank capacity(L)	3.6	3.6	6
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L × W × H(mm × mm × mm)	470 × 385 × 450	515 × 385 × 450	635 × 445 × 550
	净重 Net weight(kg)	27	30	47
	毛重 Gross weight(kg)	29	32	49

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

汽油高压泵机组

HIGH PRESSURE PUMP

▶ HP15

▶ HP20



技术规格 Specifications

机型 Water pump model		HP15	HP20
高压泵 HIGH PRESSURE PUMP	扬程 Pump lift (m)	71	55
	吸程 Suction height (m)	6	3
	最大抽水量 Max.pump output (L/min)	430	480
发动机 ENGINE	型号Model	CS160	CS200
	连续工作时间 Continuous operating hours(h)	2.8	2.4
	燃油箱容量Fuel tank capacity(L)	3.6	3.6
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	470 x 385 x 450	515 x 385 x 450
	净重 Net weight(kg)	27	31
	毛重 Gross weight(kg)	29	33

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

高压清洗机

HIGH PRESSURE WASHER

- CSCM-120
- CSCM-170
- CSCM-200
- CSCM-240



技术规格 Specifications

清洗机	型号Model	CSCM-120	CSCM-170	CSCM-200	CSCM-240
PREMIUM PRESSURE WASHER	压力 Pressure (psi)	1700	2400	2700	3000
	最大压力Max.Pressure (psi)	2000	2700	3000	3200
	流量Flow (GPM)	2.0	2.2	3.0	3.5
发动机 ENGINE	型号Model	CS160	CS160	CS200	CS270
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke			
	排气量Displacement(ml)	163	163	196	270
	最大输出功率Max.output(HP/rpm)	5.5/3600	5.5/3600	6.5/3600	9.0/3600
	燃料Fuel	无铅汽油 Unleaded gasoline			
	燃油箱容量Fuel tank capacity(L)	3.6	3.6	3.6	6
	机油Oil	SF或更高级的机油 SF or Higher grade			
	机油容量Oil capacity(L)	0.6	0.6	0.6	1.1
	点火系统Ignition system	无触点晶体管点火 T.C.I			
	启动系统 Starting system	反冲手拉起动Recoil and hand-operated			
标准装备 STANDARD FEATURES	喷嘴 Nozzle	0	0	0	0
	喷枪 Spray gun	0	0	0	0
	出水管 Water outlet hose	0	0	0	0
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L×W×H(mm×mm×mm)	640×510×580	640×510×580	640×510×580	720×670×580
	净重 Net weight(kg)	32	35	37	49
	毛重Gross weight(kg)	35	38	40	52

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

垂直轴汽油机

VERTICAL SHAFT GASOLINE ENGINE

➤ CSV120

➤ CSV140

➤ CSV160



技术规格 Specifications

型号 Model	CSV120	CSV140	CSV160
发动机型式 (Engine type)	单缸、四冲程 4-stroke, single cylinder with Air-cooled		
缸径 × 行程 Bore × Stroke (mm × mm)	60 × 42	64 × 42	68 × 45
气缸排量 Displacement(ml)	118	135	163
压缩比 Compression ratio	8: 1	8: 1	8.5: 1
最大输出功率 Max.output (HP/rpm)	4.0/3600	4.5/3600	5.5/3600
最大扭矩 Max.torque (N.m/rpm)	8.4/2500	9.0/2500	10.8/2500
点火系统 Ignition system	无触点晶体管点火T.C.I		
起动方式 Start mode	反冲式手拉起动 Recoil and hand-operated		
空气滤清器 Air cleaner	半干、油浴、双式、双静噪、旋风滤 Semi-dry, oil bath, double silent and cyclone type		
燃油箱容量 Fuel tank capacity(L)	1	1	1
耗油量 Fuel consumption(g/HP.h)	270		
机油容量 Engine oil capacity(L)	0.6		
尺寸 Dimensions(L × W × H)(mm × mm × mm)	375 × 330 × 335	400 × 350 × 330	415 × 359 × 354
净重 Net weight(Kg)	12.5	13	14.6

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

割草机

LAWN MOWER

➤ CSS480A

➤ CSZ480A

➤ CSS530A

➤ CSZ530A



技术规格 Specifications

型号Model	CSS480A	CSZ480A	CSS530A	CSZ530A
动力 Engine	CSV120		CSV160	
推行方式 Push type	手推式 Push by hand	自走式 Self-propelled	手推式 Push by hand	自走式 Self-propelled
推行速度Push speed(m/s)	0.8-1.2			
割草直径 Diameter of mowing(mm)	480		530	
修剪高度Height of mowing(mm)	16-76		25-110	
工作效率Working efficiency(m ² /h)	1400-2100		1500-2300	
集草方式Grass collection	大型集草袋Big bag			
总尺寸 Dimensions L x W x H(mm x mm x mm)	1450×460×950		1600×590×1100	
净重 Net weight(kg)	30	33	38	42
毛重 Gross weight(kg)	33	36	41	45

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

柴油机

DIESEL ENGINE

▶ CS170F

▶ CS178F

▶ CS178FS



技术规格 Specifications

型号 Model	CS170F	CS178F	CS178FS
发动机型式 (Engine type)	单缸、四冲程、强制风冷 4-stroke, single cylinder with Air-cooled		
缸径 × 行程 Bore × Stroke (mm × mm)	70 × 55	78 × 62	78 × 62
发动机转速 Engine speed(rpm)	3000/3600	3000/3600	1500/1800
气缸排量 Displacement(ml)	211	296	296
压缩比 Compression ratio	20:1		
最大输出功率 Max.output (HP/rpm)	3.8/3600	5.5/3600	5.5/1800
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start		
燃油 Fuel	0# -- 10#柴油 / 0# or -10# light diesel oil		
燃油箱容量 Fuel tank capacity(L)	2.5	3.5	3.5
耗油量 Fuel consumption(g/kW.h)	285	283	283
机油容量 Engine oil capacity(L)	0.8	1.1	1.1
尺寸 Dimensions(L × W × H)(mm × mm × mm)	420 × 380 × 470	480 × 460 × 520	480 × 460 × 520
净重 Net weight(Kg)	26	33	33
毛重 Gross weight(Kg)	29	36	36

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

柴油机

DIESEL ENGINE



CS186F



CS186FS



CS186FA



技术规格 Specifications

型号 Model	CS186F	CS186FS	CS186FA
发动机型式 (Engine type)	单缸、四冲程、强制风冷 4-stroke, single cylinder with Air-cooled		
缸径 × 行程 Bore × Stroke (mm × mm)	86 × 70	86 × 70	86 × 72
发动机转速 Engine speed(rpm)	3000/3600	1500/1800	3000/3600
气缸排量 Displacement(ml)	406	406	418
压缩比 Compression ratio	19:1		
最大输出功率 Max.output (HP/rpm)	8.6/3600	8.6/1800	9/3600
起动方式 Start mode	反冲式手拉起动/电起动 Recoil and hand-operated/Electric start		
燃油 Fuel	0# --10#柴油 / 0# or -10# light diesel oil		
燃油箱容量 Fuel tank capacity(L)	5.5	5.5	5.5
耗油量 Fuel consumption(g/kW.h)	280	280	280
机油容量 Engine oil capacity(L)	1.65	1.65	1.65
尺寸 Dimensions(L × W × H)(mm × mm × mm)	500 × 475 × 555	500 × 475 × 555	500 × 475 × 555
净重 Net weight(Kg)	48	48	48
毛重 Gross weight(Kg)	51	51	51

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

柴油水泵机组

DIESEL WATER PUMP

➤ DWP20

➤ DWP30

➤ DWP40



技术规格 Specifications

机型 Water pump model		DWP20	DWP30	DWP40
水泵 WATER PUMP	进、出水管内径 Inlet and outlet inside diameter (mm)	50 (2 inch)	80 (3 inch)	100 (4 inch)
	扬程 Pump lift (m)	15	13	16
	吸程 Suction height (m)	8	8	8
	最大抽水量 Max.pump output (L/min)	370	500	670
发动机 ENGINE	型号Model	CS170F	CS178F	CS186F
	连续工作时间 Continuous operating hours(h)	3.0	2.6	2.6
	燃油箱容量Fuel tank capacity(L)	2.5	3.5	5.5
包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	525 x 410 x 515	570 x 445 x 550	650 x 480 x 600
	净重 Net weight(kg)	39	49	62.5
	毛重 Gross weight(kg)	42	52	65.5

图片仅供参考，产品设计与规格如有更改，恕不另行通知

Specifications subject to change without notice

柴油发电机组

DIESEL GENERATOR



➤ CD2500

➤ CD3500

技术规格 Specifications

发电机 GENERATOR	型号Model	CD2500	CD3500
	类型Type	单相 single-phase	
	电压调节Voltage regulate	自动电压调节 AVR	
	频率Frequency (Hz)	50/60	
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240	
	额定交流输出功率Rated AC Output(KW)	1.7/2.0	2.8/3.0
	最大交流输出功率Peak AC Output(KW)	2.0/2.3	3.0/3.3
	功率因数Power factor	COS φ=1	
发动机 ENGINE	型号Model	CS170F	CS178F
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke	
	排气量Displacement(ml)	211	296
	最大输出功率Max.output(HP/rpm)	3.8/3600	5.5/3600
	压缩比Compression ratio	20:1	
	燃料Fuel	0# -- -10#柴油 / 0# or -10# light diesel oil	
	连续工作时间 Continuous operating hours(h)	9	8
	耗油量 Fuel consumption(g/kW.h)	285	283
	启动系统 Starting system	反冲手拉起动/电起动Recoil and hand-operated/ Electric start	
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	80	
	包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	660 x 480 x 540
净重 Net weight(kg)		60	70
毛重Gross weight(kg)		65	75

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

柴油发电机组

DIESEL GENERATOR



➤ CD5500

➤ CD6500

技术规格 Specifications

发电机 GENERATOR	型号Model	CD5500	CD6500
	类型Type	单相 single-phase	
	电压调节Voltage regulate	自动电压调节 AVR	
	频率Frequency (Hz)	50/60	
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240	
	额定交流输出功率Rated AC Output(KVA)	4.2/4.6	4.5/4.8
	最大交流输出功率Peak AC Output(KVA)	4.5/5.0	5.0/5.5
	功率因数Power factor	COS $\phi=1$	
发动机 ENGINE	型号Model	CS186F	CS186FA
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke	
	排气量Displacement(ml)	406	418
	最大输出功率Max.output(HP/rpm)	8.5/3600	9/3600
	压缩比Compression ratio	19:1	
	燃料Fuel	0# -- -10#柴油 / 0# or -10# light diesel oil	
	连续工作时间 Continuous operating hours(h)	6.5	6
	耗油量 Fuel consumption(g/kW.h)	280	
	启动系统 Starting system	反冲手拉起动/电起动机Recoil and hand-operated/ Electric start	
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	80	
	包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	740 x 500 x 660
净重 Net weight(kg)		95	95
毛重Gross weight(kg)		100	100

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice

柴油发电机组

DIESEL GENERATOR



➤ CD3500SEL

➤ CD6500SEL

技术规格 Specifications

发电机 GENERATOR	型号Model	CD3500SEL	CD6500SEL
	类型Type	单相 single-phase	
	电压调节Voltage regulate	自动电压调节 AVR	
	频率Frequency (Hz)	50/60	
	额定交流电压Rated AC Voltage (V)	110/120/220/230/240	
	额定交流输出功率Rated AC Output(KW)	2.8/3.0	4.5/4.8
	最大交流输出功率Peak AC Output(KW)	3.0/3.3	5.0/5.5
	功率因数Power factor	COS φ=1	
发动机 ENGINE	型号Model	CS178F	CS186FA
	类型Type	强制空冷, 四冲程 OHV Forced Air-cooled 4-Stroke	
	排气量Displacement(ml)	296	418
	最大输出功率Max.output(HP/rpm)	5.5/3600	9/3600
	压缩比Compression ratio	20:1	
	燃料Fuel	0# - -10#柴油 / 0# or -10# light diesel oil	
	连续工作时间 Continuous operating hours(h)	8	6
	耗油量 Fuel consumption(g/kW.h)	283	280
	启动系统 Starting system	反冲手拉起动/电起动Recoil and hand-operated/ Electric start	
	操作噪音等级 (7米) Operating noise level(7m)dB(A)	80	
	包装尺寸 PACKAGE DIMENSION	总尺寸 Dimensions L x W x H(mm x mm x mm)	830×532×740
净重 Net weight(kg)		140	175
毛重Gross weight(kg)		160	195

图片仅供参考, 产品设计与规格如有更改, 恕不另行通知

Specifications subject to change without notice